



Dollies



JT2 GROUP

Ground Support Equipment

Dollies Specification

Baggage dolly

EP 1600 BD

- Dimension of loading surface: 2400 x 1400 mm
- Height of loading surface: 520 mm
- Capacity: 1600 kg
- V shaped antislip loading surface
- Manual rear hitch
- Solid tyres
- Hot dip galvanization for rust protection



Options available:

- Side doors
- Canvas Cover
- Rear automatic hitch
- Various dimensions of loading surface available upon request
- Various types of covers available upon request

Container dolly

EP 1600 CD

For transport and manipulation of 60.4 "x61.5", 60.4 „x47“ containers.

- Capacity: 1600 kg
- Width: 1840 mm
- Length (tow bar up/down): 2685/3730 mm
- Locks for load securing
- Manual or automatic rear hitch
- Solid tyres
- 360° turnable loading surface with locks on every 90°
- Walkways made from antislip steel sheets S235 JR EN10025

Slavepallet

EP 7000 SP

For transport and manipulation of PAG and PMC pallets.

- Capacity: 7000 kg
- Width: 2540 mm
- Length: 3330 mm
- Locks for load securing
- High capacity rolls - 56 pcs
- Pockets for forklift
- Robust durable construction made from welded steel profiles and tubes
- Hot dip galvanization for rust protection
- Walkways made from antislip steel sheets S235 JR EN10025

Pallet dolly

EP 7000 PD

For transport and manipulation of: 88"x125", 96"x125", 88"x108" - pallets LDI, LD2, LD3, 60.4 "x61.5", 60.4 „x47“, 60.4 „, x125“ - containers.

- Capacity: 7000 kg
- Width: 3322 mm
- Length (tow bar up/ down): 3100/ 4340 mm
- Locks for load securing
- Manual rear hitch
- Tandem solid tyres
- Walkways made from antislip steel sheets S235 JR EN10025

All these products can be manufactured in accordance to the customer requests.



Pallet dolly

EP 14000 PD

For transport and manipulation of 96"x238.5" pallets.

- Capacity: 14000 kg
- Width: 2560 mm
- Length (tow bar up/down): 7325/8480 mm
- Locks for load securing
- Manual rear hitch
- Tandem solid tyres
- Walkways made from antislip steel sheets S235 JR EN10025

Rack

EP14000R

For storing pallets and containers.

- Capacity: 14000 kg
- One or multiple levels
- High capacity rolls
- Robust durable construction made from welded steel profiles and tubes
- Hot dip galvanization for rust protection

JT2 GROUP
Ground Support Equipment

Your Success is our Goal.

**We offer better, faster, more effective ways
to get the job done.**



JT2 GROUP
Ground Support Equipment

Main Office

JT2 Group GmbH
Münchner Str. 19a
82319 Starnberg
Germany

Communication

Telephone: +49 (0)8151 / 99 86 79 - 0
Fax: +49 (0)8151 / 99 86 79 - 9
Email: info@JT2Group.com
Web: www.JT2Group.com